

## MFE 40 (604040590) Wall chaser (220-240 V / 50 - 60 Hz); Plastic Carry Case

Order no. 604040590  
EAN 4007430327628



Product may differ from Image



- Ideal for electric installations to lay cables and pipework under plaster with cutting depths up to 40 mm
- Maximum work progress by means of powerful motor, constant speed and two-speed high-performance gear
- Robust aluminium die-cast hood with rubber rollers and optimal handle position for comfortable guidance of the machine
- Push cut for optimal view of the marking line
- Channel width and cutting depth can be set
- Metabo Marathon motor with patented dust protection for long service life
- Tacho-Constamatic (TC)-Full Wave Electronics: fast work progress by means of constant speed under load
- Electronic soft start and restart protection for safe working
- LED signal informs about overload or active restart protection
- Clean, low-dust working by means of connecting a Metabo all-purpose vacuum cleaner (certified with ASR 35 M ACP)
- Suitable for slitting grooves up to a width of 30 mm without centre in one workstep (with special accessories)
- Also suitable for cutting with only one diamond cutting disc
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the disc stop unexpectedly

## Technical data

### Characteristics

|                              |                                                                  |
|------------------------------|------------------------------------------------------------------|
| Adjustable cutting depth     | 10 - 40 mm // 3/8 - 1 9/16 "                                     |
| Possible groove widths       | 9 / 15.5 / 22 / 28.5 / 35 mm / 3/8 / 5/8 / 7/8 / 1 1/8 / 1 3/8 " |
| Cutting disc Ø               | 125 mm / 5 "                                                     |
| Rated input power            | 1900 W                                                           |
| Output power                 | 1120 W                                                           |
| No-load speed                | 5000 rpm                                                         |
| Speed at rated load          | 4200 rpm                                                         |
| Torque                       | 6 Nm / 53 in-lbs                                                 |
| Weight (without power cable) | 4.6 kg / 10.1 lbs                                                |
| Cable length                 | 4 m / 13 ft                                                      |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Vibration                    | 5.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 93 dB(A)  |
| Sound power level (LwA)      | 104 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Spacer Rings  
 Face pin wrench  
 Chase chisel  
 Plastic carry case  
 2 Diamond cutting discs  
 Flange nut